

OWNER OF RECORD

N/F FREEMAN J. AND MAUREEN
F. CONDON
REVOCABLE TRUST
BK. 21338 PG. 332

N/F FREEMAN J. AND MAUREEN
F. CONDON
REVOCABLE TRUST
BK. 21338 PG. 324

TOTAL AREA 1,173,380 S.F. 26.94 ACRES

PLAN INDEX


1 27 (14 1142	JEX
SHEET NO.	TITLE
C-1	COVER SHEET
C-2-3	EXISTING CONDITIONS PLAN
C-4	LEGEND/NOTES
C-5-7	GRADING PLANS
C-8-10	UTILITY PLAN & PROFILE
C-11	SITE DETAILS
C-12	SEWER DETAILS
C-13	DRAINAGE DETAILS
C-14	DRAINAGE/EROSION CONTROL DETAILS
C-15	WETLAND REPLICATION DETAILS
C-16	SOIL LOGS
E-1-2	LIGHTING PLAN
F-1-2	FIRE TRUCK TEMPLATE
L-1	LANDSCAPE PLAN
A1	ARCHITECTURAL PLAN

"MEADOWVIEW AT SALISBURY" CONDOMINIUM


6 FOREST ROAD & MEADOWVIEW LANE


IN SALISBURY, MA

APRIL 2021



NO. DATE





6 FOREST ROAD LLC
71 COMMERCIAL STREET, #263
BOSTON, MA 02109

PREPARED FOR

				M
1	4/12/21	ADDRESS REVIEWER'S COMMENTS	C.M.Y.	SCA

DESCRIPTION

MILLENNIUM ENGINEERING, INC.
ENGINEERING AND LAND SURVEYING
62 ELM ST. SALISBURY, MA 01952 (978) 463-8980
13 HAMPTON RD. EXETER, NH 03833 (603) 778-0528

DESG. BY: C.M.Y.

CHKD. BY: E.W.B.

BY DATE: OCT. 26, 2020

ROJECT: M193659

PLAN OF LAND
IN
SALISBURY, MA
SHOWING

COVER SHEET

64 UNIT TOWNHOUSE COMMUNITY

AT

6 FOREST ROAD & MEADOWVIEW LANE

SHEET

ZONING TABLE

6 FOREST ROAD - ASSESSORS MAP 20 LOTS 43, 44, 45 & 91 ZONING DISTRICT R-1

6 FOREST ROAD - ASSESSORS MAP 20 LOTS 43, 44, 45 & 91 ZONING DISTRICT R-2

26.94 ACRES

725.26 FEET

10.9 FEET

150.8 FEET

1012.4 FEET

EXISTING

26.94 ACRES

725.26 FEET

10.9 FEET

150.8 FEET

1012.4 FEET

26.94 ACRES

725.26 FEET

112.6 FT

21.5 FT

21.7 FT

6.1%

< 35 FEET

PROPOSED

26.94 ACRES

725.26 FEET

112.6 FT

21.5 FT

21.7 FT

6.1%

< 35 FEET

REQUIRED

2 ACRES

200 FEET

40 FEET

20 FEET

20 FEET

20% MAX

N/A

35 FEET

REQUIRED

1 ACRES

150 FEET

20 FEET

20 FEET


25% MAX


N/A


35 FEET

SHEET: C-1

E:\sdskproj-2019\M193659\dwg\M193659-D.dwg 4/9/2021 1:52:20 PM EDT







ROADWAY CROSS-SECTION

STA. 0+00 TO STA. 22+00±

CATCH BASIN (OR GUTTER INLET, OR LEACHING BASIN)

CATCH BASIN (OR GUTTER INLET) WITH CURB INLET

CURB (OR BERM) - TYPE NOTED

POST MOUNTED PEDESTRIAN LIGHT

EDGE OF ROAD

SEWER MANHOLE DRAINAGE MANHOLE

CONTOUR

GAS GATE

WATER GATE

SEPTIC TANK

UTILITY POLE DRAIN PIPE

SEWER MAIN

MAIL BOX

SEWER FORCE MAIN


UNDERGROUND ELECTRIC

HIGHWAY GUARD (TYPE NOTED)

FIRE ALARM BOX


HYDRANT

N.T.S.



NOTES:

- 1. RAMP CROSS SECTION TO BE SAME AS SIDEWALK; I.E. DEPTH OF SURFACE AND FOUNDATION.
- 2. PORTLAND CEMENT CONCRETE RAMPS ARE TO BE TEXTURED BY BROOMING IN A DIRECTION PARALLEL TO THE LENGTH OF THE RAMP.
- 3. BASE OF RAMP SHALL MEET PAVEMENT GUTTER SUCH THAT THERE IS NO DIFFERENCE IN ELEVATION. RAMP SHALL BE CONSTRUCTED SUCH THAT WATER DOES NOT "PUDDLE" AT THE BASE OF THE RAMP.
- 4. THE PAVEMENT AT THE BASE OF THE RAMP SHALL BE PART OF THE CONTINUOUS TOP COURSE. THE USE OF A "PAVEMENT PATCH" TO COMPLY WITH THE CONDITIONS IN NOTE 3, ABOVE IS PROHIBITED
- 5. RAMPS SHALL CONFORM TO MASS DOT WHEELCHAIR RAMP STANDARDS LATEST REVISION.



	DADWAY ILE GRADE	HIGH SIDE
 PRUF	ILE GRADE	TRANSITION LENGTH
%	G	ENGLISH UNITS
0	0.00	6'-6"
1	0.01	7'-8"
2	0.02	9'-0"
3	0.03	11'-0"
4	0.04	14'-0"
>4	>0.04	15'-0" MAX

A.D.A. ACCESS RAMP DETAIL

N.T.S.

GRANITE CURB TYPE VB— 6" REVEAL TYP.
6" LOAM & SEED - 5"
6"-/ -12" GRAVEL
CEMENT CONCRETE

TYPICAL GRANITE **CURBING DETAIL**

N.T.S.

GENERAL NOTES

(MDOT SECT. M4)

FENCE (SIZE AND TYPE NOTED) EASEMENT LINE PROPERTY LINE

LEGEND

PROPOSED

CBCI (OR GICI)

____(108)_____

EXISTING

OFA

----UE----

 $\square MB$

× N00°00'00"

SURVEY

120 8

□ C.B.

D.H.

O 1.P.

● I ROD

FND.

N/FND.

+12.34

. . .

---- 100 FT BUFFER ZONE BASE OR SURVEY LINE N000000E CONSTRUCTION BASELINE

WHEELCHAIR RAMP (WCR) CONCRETE SIDEWALK

WETLAND DELINEATION FLAG

ASSESSORS MAP AND PARCEL

CONCRETE BOUND

STONE BOUND

DRILL HOLE


IRON PIPE

IRON ROD

NOT FOUND

FOUND

MASONRY NAIL



1. THE CONTRACTOR SHALL REPORT TO THE OWNER AND ENGINEER ANY SIGNIFICANT VARIATIONS IN EXISTING SITE CONDITIONS. ANY PROPOSED REVISIONS TO THE WORK SHALL NOT BE UNDERTAKEN UNTIL REVIEWED AND APPROVED BY THE OWNER AND REGULATING CITY AND/OR STATE AGENCIES.

- 2. THE CONTRACTOR SHALL INSTALL ALL SYSTEM COMPONENTS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS AND ALL APPLICABLE ELECTRICAL, PLUMBING, AND SANITARY CODES.
- 3. ALL WORK SHALL CONFORM TO; THE SALISBURY PLANNING BOARD RULES AND REGULATIONS GOVERNING THE SUBDIVISION OF LAND, THE WETLANDS PROTECTION ACT (310 CMR 10.00), THE ORDER OF CONDITIONS ISSUED BY THE SALISBURY CONSERVATION COMMISSION, AND THESE PLANS.
- 4. THE LOCATION OF ALL UTILITIES, AS SHOWN ON THESE PLANS, ARE BASED UPON PLANS AND RECORD INFORMATION PROVIDED BY MUNICIPAL AND PRIVATE UTILITY COMPANIES AND ARE CONSIDERED APPROXIMATE BOTH AS TO SIZE AND LOCATION. NO WARRANTY IS MADE AS TO THE ACCURACY OF THESE LOCATIONS OR THAT ALL UTILITIES ARE SHOWN. THE CONTRACTOR SHALL NOT RELY ON THESE PLANS FOR SUCH INFORMATION AND WILL MAKE EXAMINATIONS IN THE FIELD BY VARIOUS AVAILABLE RECORDS, UTILITY COMPANIES AND INDIVIDUALS, AS TO THE LOCATION OF ALL SUBSURFACE STRUCTURES.
- 5. THE CONTRACTOR SHALL VERIFY THE LOCATION OF EXISTING UTILITIES BY CONTACTING "DIG-SAFE" AT LEAST 72 HOURS PRIOR TO ANY EXCAVATION. DIG-SAFE TELEPHONE NUMBER: 1-888-344-7233.
- 6. THE CONTRACTOR SHALL FIELD CHECK ALL DIMENSIONS AND ELEVATIONS BEFORE PROCEEDING WITH THE NEW WORK. HE/SHE SHALL EXCAVATE TO VERIFY PERTINENT DRAINAGE INVERTS AND POTENTIAL UTILITY CONFLICTS. ANY DISCREPANCIES SHALL BE REPORTED TO THE OWNER IMMEDIATELY.
- 7. ALL EXISTING STRUCTURES AND SURFACES, UNLESS OTHERWISE SHOWN, SHALL BE COMPLETELY REMOVED FROM THE AREAS OF WORK. ALL TREES SCHEDULED FOR REMOVAL SHALL BE FIELD MARKED AND APPROVED FOR REMOVAL BY THE OWNER PRIOR TO CUTTING OPERATIONS.
- 8. THE CONTRACTOR IS RESPONSIBLE FOR INITIATING, MAINTAINING AND SUPERVISING ALL SAFETY PRECAUTIONS AND PROGRAMS IN CONNECTION WITH THE WORK. THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS FOR THE SAFETY OF THE PUBLIC. EMPLOYEES, AND ALL OTHER PERSONS ASSOCIATED WITH THE PROJECT. HE/SHE SHALL COORDINATE AND BE RESPONSIBLE FOR ALL SAFETY SIGNING, BARRIERS AND TEMPORARY PAVEMENT MARKINGS NECESSARY TO PROVIDE A SMOOTH AND PROPER TRANSITION FOR TRAFFIC FLOW.
- 9. IF REQUIRED BY THE CONTRACTOR, OVERHEAD LINES SHALL BE RELOCATED BY THE UTILITY COMPANY AT THE CONTRACTORS EXPENSE.

- 10. ALL SEWER MAINS AND SERVICES SHALL BE INSTALLED AT LEAST 10 FEET HORIZONTALLY OR 18 INCHES VERTICALLY FROM PROPOSED WATER MAINS AND SERVICES AND SHALL MAINTAIN 5 FEET OF COVER OVER THE TOP OF THE PIPING, UNLESS OTHERWISE SHOWN OR APPROVED. PIPES SHALL BE ENCASED IN CONCRETE WHERE THIS SEPARATION CANNOT BE OBTAINED.
- 11. ALL WATER MAINS SHALL BE INSTALLED WITH A MINIMUM OF 5 FEET OF COVER OVER THE TOP OF THE PIPE, UNLESS OTHERWISE SHOWN OR APPROVED.
- 12. WHENEVER SEWER MAINS MUST CROSS WATER MAINS, THE SEWER SHALL BE CONSTRUCTED AS FOLLOWS; A) JOINTS SHALL BE MECHANICAL TYPE WATER PRESSURE RATED WITH ZERO LEAKAGE WHEN TESTED AT 25 PSI FOR GRAVITY SEWERS AND 1.5 TIMES WORKING PRESSURE FOR FORCE MAINS AND JOINTS NOT TO BE LOCATED WITHIN 9 FEET OF THE CROSSING: B) SEWER SERVICES SHOULD BE INSTALLED A MINIMUM OF 18 INCHES BELOW WATER MAINS. IF SEPARATION IS LESS THAN 18 INCHES, SEWER SERVICE SHALL BE CONCRETE ENCASED OR CONSTRUCTED WITH PRESSURE CLASS PVC FOR A DISTANCE OF 10 FEET EACH SIDE OF THE WATER MAIN. 10-FOOT MINIMUM HORIZONTAL SEPARATION DISTANCE SHALL BE
- 13. INDIVIDUAL BUILDING OWNERS ARE RESPONSIBLE FOR MAINTENANCE OF THEIR SEWER SERVICE FROM THE BUILDING TO THE CONNECTION TO THE SEWER MAIN.
- 14. ALL SIGNS AND PAVEMENT MARKINGS TO BE INSTALLED WITHIN THE PROJECT SITE SHALL CONFORM TO THE APPLICABLE SPECIFICATIONS OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD).
- 15. 14 DAYS PRIOR TO COMMENCING CONSTRUCTION, THE OWNER/DEVELOPER SHALL PRESENT A CONSTRUCTION SCHEDULE TO THE PLANNING
- 17. THE OWNER/DEVELOPER SHALL SUBMIT TWO HARD COPIES OF AS-BUILT DRAWINGS TO THE PLANNING BOARD WITHIN 90 DAYS OF ISSUANCE OF OCCUPANCY PERMIT. AS-BUILTS SHALL INCLUDE ALL LANDBASE AND UTILITIES INFORMATION.
- 18. ONSITE BURIAL OF STUMPS OR ANY OTHER DEBRIS IS PROHIBITED.
- 19. THE REAR OF THE PROPERTY BY SMALLPOX BROOK LIES WITHIN THE 100-YEAR FLOOD PLAIN ACCORDING TO F.I.R.M. COMMUNITY PANEL NUMBER 25009C 0126F.

C.M.Y.

20. ALL ELEVATIONS ARE BASED ON N.A.V.D. 1988.

NO. DATE

SIDEWALK NOTES

SIDEWALKS SHALL BE FIVE FEET IN WIDTH FOR THEIR ENTIRE LENGTH, WITH A 1% CROSS SLOPE (1.5% MAX).

SIDEWALKS SHALL BE CONSTRUCTED WITH A 1.5" TYPE I-1 BITUMINOUS CONCRETE FINISH COURSE, A 1.5" TYPE I-1 BITUMINOUS CONCRETE BINDER COURSE OVER AN 8" GRAVEL BASE (MDOT M1.03.0 TYPE B).

WHERE SIDEWALKS TRAVERSE A DRIVEWAY, THE GRAVEL BASE SHALL BE 12" THICK.

MATERIAL NOTES

ALL MATERIALS OF THE ELEMENTS IN THE SITE PLAN MUST CONFORM TO THE FOLLOWING STANDARDS:

- COMMONWEALTH OF MASSACHUSETTS DEPARTMENT OF TRANSPORTATION
- STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES (LATEST EDITION) 2. 521 CMR RULES AND REGULATIONS OF THE ARCHITECTURAL ACCESS BOARD
- (AAB) AND THE AMERICANS WITH DISABILITIES ACT (ADA) 3. SPECIFICATIONS BY THE TOWN OF SALISBURY AS SET FORTH BY SECTION 7 IN THE PLANNING BOARD RULES AND REGULATIONS GOVERNING THE
- SUBDIVISION OF LAND, DATED NOVEMBER 1, 2013 4. UTILITIES INSTALLED PER PENNICHUCK WATER SERVICE CORPORATION SPECIFICATIONS

ROADWAY NOTES

- 1.) ALL STUMPS, ROCKS AND LEDGE WITHIN THE LIMITS OF THE PROPOSED PAVED WAY SHALL BE REMOVED. ALL LEDGE SHALL BE REMOVED TO A MINIMUM DEPTH OF 2' BELOW FINISHED PAVEMENT GRADE.
- 2.) ROADWAY SHALL NOT BE CONSTRUCTED DURING FREEZING WEATHER OR ON WET OR FROZEN SUBGRADE.
- 3.) GRADING AND ROLLING SHALL BE REQUIRED TO PROVIDE A SMOOTH, EVEN, AND UNIFORM COMPACTED BASE WHICH IS COMPACTED TO A MINIMUM DRY DENSITY OF
- 4.) THE MINIMUM SLOPE FROM THE CROWN OF FINISHED BASE COURSE SHALL BE 1/4"PER FOOT UNLESS OTHERWISE SHOWN.
- 5.) ALL UNSUITABLE MATERIAL SHALL BE EXCAVATED AND REPLACED WITH SATISFACTORY MATERIAL AND BROUGHT UP TO GRADE WITH GRAVEL BORROW CONTAINING NO STONES GREATER THAN 6" DIAMETER.
- 6.) AT ALL TIMES DURING CONSTRUCTION, THE SUB-GRADE AND ALL DITCHES SHALL BE CONSTRUCTED AND MAINTAINED SO THAT THE ROADWAY WILL EFFECTIVELY BE DRAINED.
- 7.) THE CONTRACTOR SHALL REFER TO THE SALISBURY PLANNING BOARD RULES AND REGULATIONS GOVERNING THE SUBDIVISION OF LAND, SECTIONS I - VII.

CHRISTOPHER M. YORK CIVIL No. 49161

6 FOREST ROAD LLC

PREPARED FOR

71 COMMERCIAL STREET, #263 BOSTON, MA 02109

	N
	ME
	1

4/12/21 | ADDRESS REVIEWER'S COMMENTS

DESCRIPTION

SCALE: AS NOTED

DATE: OCT. 26, 2020

MILLENNIUM ENGINEERING, INC. ENGINEERING AND LAND SURVEYING

DESG. BY: C.M.Y.

CHKD. BY: E.W.B

62 ELM ST. SALISBURY, MA 01952 (978) 463-8980 13 HAMPTON RD. EXETER, NH 03833 (603) 778-0528

SALISBURY, MA SHOWING

PROJECT: M193659


64 UNIT TOWNHOUSE COMMUNITY 6 FOREST ROAD & MEADOWVIEW LANE


PLAN OF LAND


TYPICAL SECTIONS/ LEGEND/ GENERAL NOTES


SHEET: C-4


E:\sdskproj-2019\M193659\dwg\M193659-D.dwg 4/9/2021 1:52:20 PM EDT



























NOTES: 1) SEWER MANHOLES SHALL CONFORM TO ASTM C478 AND ASTM C185
2) STEEL REINFORCED COPOLYMER POLYPROPYLENE PLASTIC
STEPS SHALL CONFORM TO LATEST ASTM C478 SPEC.
3) COVER SHALL BE LEBARON FOUNDRY (MODEL NO. LA246),
MECHANICS IRON FOUNDRY, NEEHAN FOUNDRY, OR EQUAL.

PRECAST SEWER

MANHOLE DETAIL N.T.S.



NOTES:

- 1. CONCRETE: 5,000 PSI MINIMUM AFTER 28 DAYS.
- REINFORCED STEEL CONFORMS TO LATEST ASTM A185 SPEC. 0.12 SQ. IN./LINEAL FT. AND 0.12 SQ. IN. (BOTH WAYS) BASE BOTTOM.
- 3. H-20 DESIGN LOADING PER AASHTO HS-20-44; ASTM C478 SPEC FOR "PRECAST REINFORCED CONCRETE MANHOLE SECTIONS."
- 4. BUTYL RESIN SECTION JOINT CONFORMS TO LATEST ASTM C443 SPEC.
- 5. STEEL REINFORCED COPOLYMER POLYPROPYLENE PLASTIC
- STEPS SHALL CONFORM TO LATEST ASTM C478 SPEC.

 6. A SIGN SHALL BE ADDED IN THE MANHOLE STATING "DO NOT CONNECT TO MUNICIPAL WATER SYSTEM TO FLUSH FORCE

FORCE MAIN

CLEANOUT DETAIL N.T.S.



THE SEWER DEPARTMENT SHALL BE NOTIFIED 48 HOURS BEFORE ALL TESTING TAKES PLACE IN ORDER THAT A REPRESENTATIVE OF THE DEPARTMENT OF PUBLIC SERVICES CAN BE PRESENT.

- TESTING PROCEDURES FOR SEWER MAINS AND INDIVIDUAL SEWER SERVICES SHALL BE AS SPECIFIED IN ASTM C828-01, C924-02, AND F1417-92 (OR LATEST REVISIONS)-STANDARD TEST METHOD FOR LOW PRESSURE AIR TEST (VCP, CP, PVCP) SEWER LINES, FURTHER AS MODIFIED BY THE ALLOWABLE PRESSURE LOSS SHALL NOT EXCEED 0.5 PSI WITHIN THE TIME REQUIREMENTS. MAINS SHALL BE MANDREL TESTED PRIOR TO ACCEPTANCE BY THE SEWER DEPARTMENT.
- 2. TESTING PROCEDURES FOR SEWER FORCE MAINS SHALL BE AS SPECIFIED IN ASTM C828-01, C924-02, AND F1417-92 (OR LATEST REVISIONS), FURTHER AS MODIFIED BY THE "STARTING TEST PRESSURE" SHALL BE A MINIMUM OF 10.0 PSI, 50% OF THE MAXIMUM RATED PRESSURE, THE ALLOWABLE PRESSURE LOSS SHALL NOT EXCEED 0.5 PSI WITHIN THE TEST TIME REQUIRED AND THE TEST TIME SHALL BE AN INITIAL 15 MINUTES FOR ALL PIPE DIAMETERS. TEST TIME SHALL BE T=(.005)D*(L-500)+15 WHERE D=DIAMETER OF PIPE IN INCHES AND L=LENGTH OF PIPE TO BE TESTED IN FEET.
- 3. TESTING PROCEDURES FOR SEWER MANHOLES AND PUMP STATION SHALL BE AS SPECIFIED IN ASTM C1244-02 (OR LATEST REVISION)—STANDARD TEST METHOD FOR CONCRETE SEWER MANHOLES BY NEGATIVE AIR PRESSURE (VACUUM) TEST, FURTHER AS MODIFIED BY THE ALLOWABLE VACUUM LOSS SHALL NOT EXCEED 1" HG WITH ONE MINUTE FOR ALL MANHOLE SIZES.

PVC SEWER COLLECTION PIPE NOTES:

- 1.) PVC PIPE, COUPLINGS, AND FITTINGS FOR GRAVITY SEWERS SHALL CONFORM TO ASTM D3034 WITH AN SDR OF 35 UNLESS OTHERWISE SHOWN ON THE PLANS.
- 2.) PVC PIPE, COUPLINGS, AND FITTINGS FOR SEWER FORCE MAINS SHALL CONFORM TO ASTM 2241 WITH AN SDR OF 21 UNLESS OTHERWISE SHOWN ON THE PLANS.
- JOINTS FOR PVC PIPE SHALL BE PUSH ON JOINTS USING PERMANENTLY BONDED ELASTOMERIC RING JOINTS.
- 4.) FORCE MAINS SHALL BE INSTALLED WITH A CONTINUOUS SLOPE BETWEEN THE HIGH AND LOW POINTS.
- 5.) ALL FORCE MAIN FITTINGS SHALL BE RESTRAINED USING SERIES 7500 RESTRAINT FOR PVC FITTINGS AS MANUFACTURED BY EBBA IRON INC. OR APPROVED EQUAL.
- 6.) CONCRETE USED FOR THRUST BLOCKS SHALL HAVE A MINIMUM STRENGTH OF 3000 PSI. THRUST BLOCKS SHALL BE PLACED AT ALL FORCEMAIN BENDS 11¹/₄ DEGREES AND GREATER, AT FITTINGS.



6 FOREST ROAD LLC

PREPARED FOR

71 COMMERCIAL STREET, #263 BOSTON, MA 02109 MILLENNIUM ENGINEERING, INC.
ENGINEERING AND LAND SURVEYING
62 ELM ST. SALISBURY, MA 01952 (978) 463–8980
13 HAMPTON RD. EXETER, NH 03833 (603) 778–0528

1 4/12/21 ADDRESS REVIEWER'S COMMENTS C.M.Y. SCALE: AS NOTED DESG. BY: C.M.Y.
NO. DATE DESCRIPTION BY DATE: OCT. 26, 2020 CHKD. BY: E.W.B.
PROJECT: M19365

SITE PLAN SALISBURY, MA

22.5° BEND-

WYE FOR NEW SEWER -

PROPOSED 8"-

PVC SEWER

8" SCREENED GRAVEL ----

SEWER SERVICE

DETAIL

SLOPE UP 1% MIN

SEWER SERVICE SHALL BE

INSTALLED WITH AT LEAST

4' OF COVER

6" SEWER SERVICE

N.T.S.


SHOWING
64 UNIT TOWNHOUSE COMMUNITY


AT
6 FOREST ROAD & MEADOWVIEW LANE

SEWER DETAILS

SHEET: C-12

E: \sdskproj-2019\M193659\dwg\M193659-D.dwg 4/9/2021 1:52:20 PM EDT






NOTES

- 1. ALL MATERIAL SHALL MEET SPECIFICATIONS BY FILTREXX OR APPROVED EQUAL.
- 2. SILT SOCK SHALL BE INSPECTED WITHIN 24 HOURS AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL. ANY REPAIRS THAT ARE REQUIRED SHALL BE MADE IMMEDIATELY.
- 3. THE CONTRACTOR SHALL REMOVE SEDIMENT AT THE BASE OF THE UPSLOPE SIDE OF THE SILT SOCK WHEN ACCUMULATION HAS REACHED 1/2 OF THE EFFECTIVE HEIGHT OF THE SILT SOCK.
- 4. SILT SOCK SHALL BE MAINTAINED UNTIL DISTURBED AREA ABOVE THE DEVICE HAS BEEN PERMANENTLY STABILIZED AND CONSTRUCTION ACTIVITY HAS BEEN COMPLETED.
- SEDIMENT DEPOSITS THAT ARE REMOVED OR LEFT IN PLACE AFTER THE SOCK HAS BEEN REMOVED SHALL BE GRADED TO CONFORM WITH THE EXISTING TOPOGRAPHY

SILT SOCK INSTALLATION

N.T.S.




1. DURING THE ACTIVE DEWATERING PROCESS, THE STRUCTURE SHALL BE INSPECTED FREQUENTLY (E.G. ONCE PER HOUR).

2. SEDIMENT BUILDUP SHOULD BE REMOVED PERIODICALLY TO ENSURE THAT THE STRUCTURE'S ABILITY TO EFFECTIVELY FILTER SEDIMENT IS MAINTAINED.

N.T.S.

TYPICAL DEWATERING DETAIL



r=1-2 INCH DIA. WASHED,

MIN. 95% COMPACTED FILL

CRUSHED STONE

1) RECHARGER 100HD BY CULTEC, INC. OF BROOKFIELD, CT. ALL RECHARGER 150XLHD CHAMBERS MUST BE INSTALLED IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. REFER TO CULTEC, INC.'S CURRENT RECOMMENDED INSTALLATION.

CULTEC RECHARGER

100HD DETAILS

CULTEC HVLV SFCx2-


FEED CONNECTOR

CULTEC RECHARGER 100HD-

HEAVY DUTY CHAMBER

WHERE SPECIFIED

N.T.S.




- STONE SHALL BE 3-4" STONE, RECLAIMED STONE, OR RECYCLED CONCRETE EQUIVALENT.
- THE LENGTH OF THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 50'. 3. THE THICKNESS OF THE STONE FOR THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 6"
- GEOTEXTILE FILTER CLOTH SHALL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING THE STONE.
- 5. ALL SURFACE WATER THAT IS FLOWING TO OR DIVERTED TOWARD THE CONSTRUCTION ENTRANCE SHALL BE PIPED BENEATH THE ENTRANCE. IF PIPING IS IMPRACTICAL, A BERM WITH 5:1 SLOPES THAT CAN BE CROSSED BY VEHICLES MAY BE SUBSTITUTED FOR THE PIPE.
- 6. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP-DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, WASHED, OR
- TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED PROMPTLY. WHEELS SHALL BE CLEANED TO REMOVE MUD PRIOR TO ENTRANCE ONTO PUBLIC RIGHTS-OF-WAY. WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABILIZED WITH STONE WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.

STABILIZED CONSTRUCTION


ENTRANCE

N.T.S.



GENERAL EROSION CONTROL NOTES

- 1. ALL EROSION CONTROL SHALL BE INSTALLED BEFORE THE START OF CONSTRUCTION. EROSION CONTROL SHALL BE REMOVED UPON COMPLETION OF THE PROJECT AND STABILIZATION OF ALL SOIL.
- ALL FILL SHALL BE FREE OF STUMPS AND LARGE STONES.
- 3. ANY STANDING BODIES OF WATER CREATED DURING EXCAVATION SHALL BE ELIMINATED. 4. EROSION CONTROL BARRIERS SHALL BE INSPECTED WEEKLY AND AFTER EVERY 0.5" OF
- RAINFALL AND PROMPTLY REPAIRED OR REPLACED AS NECESSARY. 5. ACCUMULATED SEDIMENT DEPOSITS UPSTREAM OF BARRIERS SHALL BE PROPERLY DISPOSED
- OF ON A REGULAR BASIS. 6. AREAS OUTSIDE THE LIMITS OF WORK (EROSION CONTROL/SILT FENCE LOCATIONS) DISTURBED BY THE CONTRACTOR DURING CONSTRUCTION SHALL BE RESTORED TO THEIR ORIGINAL CONDITION AT THE
- EXPENSE OF THE CONTRACTOR. 7. THE CONTRACTOR IS RESPONSIBLE FOR MAINTAINING EROSION AND/OR SEDIMENT CONTROLS DURING CONSTRUCTION. HE/SHE SHALL INSPECT CONTROLS WEEKLY AND AFTER ALL STORM
- EVENTS. REPAIRS, IF REQUIRED, SHALL BE MADE IMMEDIATELY. 8. TEMPORARY GROUND COVER SHALL BE ESTABLISHED IN AREAS OF CONSTRUCTION WHERE
- REQUIRED BY THE SALISBURY CONSERVATION COMMISSION. 9. ANY DISTURBED AREAS OF THE SITE NOT USED FOR ROADWAY OR UTILITY CONSTRUCTION SHALL BE STABILIZED WITH LOAM AND SEED UNTIL FURTHER DISTURBANCE IS REQUIRED FOR
- BUILDING CONSTRUCTION.
- PROVIDE GRAVEL AND WIRE MESH SEDIMENT FILTER AT ALL CATCH BASINS. 11. A MINIMUM OF 6" OF LOAM SHALL BE INSTALLED ON ALL DISTURBED UNPAVED SURFACES.
- 12. PERMANENT SEED MIX SHALL BE MA STATE SLOPE MIXTURE (50% CREEPING RED FESCUE, 30% KENTUCKY 31 TALL FESCUE, 10% ANNUAL RYEGRASS, 5% RED TOP, 5% LADINO CLOVER) AND MA STATE PLOT MIXTURE (50% CREEPING RED FESCUE, 25% 85/80 KENTUCKY BLUEGRASS, 10% ANNUAL RYEGRASS, 10% RED TOP, 5% LADINO CLOVER)
- 13. NO MORE THAN 3 ACRES SHALL BE DISTURBED AT ONE TIME. ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE.
- 14. WHERE PLACEMENT OF FILL IS REQUIRED FOR STORM WATER CONTROL, FILL SHALL BE PLACED IN AN UNFROZEN STATE UPON UNFROZEN GROUND. UNDER NO CIRCUMSTANCES SHALL FILL BE PLACED FROM NOVEMBER THROUGH JANUARY.
- 15. AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED: BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED; A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED; A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED; OR EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
- 16. ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCT. 15TH, OR WHICH ARE DISTURBED AFTER OCT. 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1. AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.
- 17. ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCT. 15TH, OR WHICH ARE DISTURBED AFTER OCT. 15TH, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS.



CULTEC NO. 410 NON-WOVEN GEOTEXTILE AROUND STONE.


TOP AND SIDES ARE MANDATORY.

GUTTER DOWN SPOUT DETAIL

N.T.S.

CONSTRUCTION **SEQUENCE**

- 1. INSTALL EROSION CONTROL AT LIMIT OF WORK & STAKE OUT STORMWATER AREAS
- CONSTRUCT STABILIZED CONSTRUCTION ENTRANCE AS DEPICTED.
- 3. CLEAR AND GRUB DEBRIS TO PHASE LINE AND DISPOSE OF PROPERLY 4. STRIP, SCREEN AND STOCKPILE TOPSOIL. TOPSOIL CAN BE TEMPORARILY STOCKPILED ON SITE PROVIDING THAT THE PERIMETER OF THE STOCKPILES ARE PROPERLY STAKED
- WITH SILT FENCE AT THE TOE OF SLOPE. 5. ROUGH GRADE CONSTRUCTED WETLANDS.
- 6. GRADE PAVEMENT TO TOP OF SUBGRADE ELEVATIONS. ALL ROADWAYS MUST BE
- STABILIZED IMMEDIATELY AFTER GRADING. BEGIN BUILDING CONSTRUCTION.
- 8. INSTALL UTILITIES/DRAINAGE STRUCTURES. 9. PLACE RIPRAP WHERE SHOWN ON PLANS. LOAM AND HYDROSEED SIDESLOPES AND ALL
- DISTURBED AREAS WITHIN 72 HOURS. ADD PLANTINGS TO CONSTRUCTED WETLANDS.
- 11. SPREAD, SHAPE, AND COMPACT PAVEMENT SUBBASE AS PER TYPICAL PAVEMENT SECTION
- TO ATTAIN FINAL DESIGN ELEVATIONS. 12. PERFORM BINDER COURSE PAVING.
- 13. LOAM AND HYDROSEED ANY DISTURBED SURFACES ALONG EDGES OF PAVEMENT AS
- REQUIRED.
- 14. PERFORM FINAL PAVING (TOP COURSE).
- 15. REMOVE EROSION CONTROL.



PREPARED FOR

6 FOREST ROAD LLC

71 COMMERCIAL STREET, #263 BOSTON, MA 02109

				ENGINEERI 62 ELM ST 13 HAMPTO	IN
1	4/12/21	ADDRESS REVIEWER'S COMMENTS	C.M.Y.	SCALE: AS NOTED	
NO.	DATE	DESCRIPTION	BY	DATE: OCT. 26, 2020	

MILLENNIUM ENGINEERING, INC. ERING AND LAND SURVEYING

DESG. BY: C.M.Y.

CHKD. BY: E.W.B.

ST. SALISBURY, MA 01952 (978) 463-8980 PTON RD. EXETER, NH 03833 (603) 778-0528

SALISBURY, MA SHOWING 64 UNIT TOWNHOUSE COMMUNITY

SITE PLAN

DRAINAGE/ **EROSION** CONTROL **DETAILS**

6 FOREST ROAD & MEADOWVIEW LANE SHEET: C-14

E:\sdskproj-2019\M193659\dwg\M193659-D,dwg 4/9/2021 1:52:20 PM ED1

BVW restoration area**


Common Name	Latin Name	comments	Quantity	Plant Size	Wetland Status
plant size b	ased on avail	ability – sizes based on New England Wetland Plants – ty	ypical.		
Winterberry Holly	Ilex verticillata	Group in 6 or more, 5 to 7 feet on center	12	2-3'	FACW+
	Cornus amomum	Plant 8 to 10 feet on center with tubelings planted 3 feet on center to fill in area around and between plants	11	3-4'	FACW
Red-osier Cornus Dogwood sericea Plant 8 to 10 feet on center with tubelings planted 3 feet on center to fill in area around and between plants		11	3-4'	FACW+	
Silky Dogwood	Cornus amomum	Plant 3 feet on center around larger of same species to create dense clusters	30*	tubelings	FACW
		Plant 3 feet on center around larger of same species to create dense clusters	30*	tubelings	FACW+
Wild Raisin Viburnum Plant 4 to 6 t		Plant 4 to 6 feet on center	9*	3-4'	FACW
Highbush Vaccinium Plant 4 to 6 feet on center Blueberry corymbosum		12*	3-4'	FACW	
Red Maple Acer Plant 8 feet on center Rubrum		8	4-6'	FAC	

*Actual quantities to plant and purchase are higher, – available in trays of 38, round up for ordering

**Species and sizes may be adjusted based on plant availability

WETLAND REPLICATION PLANTING LIST

N.T.S.




WETLAND REPLICATION

AREA #2

E:\sdskproj-2019\M193659\dwg\M193659-D.dwg 4/9/2021 1:52:20 PM EDT

HORIZ. SCALE: 1"=10'




TYPICAL WETLAND REPLICATION SECTION

N.T.S.

NOTES:


- 1. THE REPLACEMENT AREA SHALL MEET STRICT PERFORMANCE STANDARDS AS LISTED UNDER 310 CMR 10.55(4)(B). CONSTRUCTION OF THE WETLAND REPLACEMENT AREA SHALL BE PERFORMED IN CONFORMANCE WITH THE ORDER OF CONDITIONS ISSUED BY THE CONSERVATION
- 2. WETLAND REPLACEMENT WORK SHALL BE SUPERVISED BY A WETLAND SCIENTIST APPROVED BY THE SALISBURY CONSERVATION COMMISSION OR ITS AGENT
- 3. THESE STANDARDS HAVE BEEN SET IN ORDER TO PROTECT THE FUNCTIONS WHICH BORDERING VEGETATED WETLANDS AND BORDERING VEGETATED WETLANDS PROVIDE. THESE STANDARDS SHALL BE MET BY ADHERING TO THE FOLLOWING CONSTRUCTION SPECIFICATIONS.
- 4. A MEETING SHALL BE SCHEDULED WITH THE CONTRACTOR AND THE WETLAND SCIENTIST PRIOR TO SITE CONSTRUCTION TO REVIEW THE CONSTRUCTION METHODOLOGY. THIS WILL INCLUDE AREAS WITHIN THE APPROVED LIMIT OF WORK FOR HARVESTING SUITABLE SOIL MATERIAL AND DESIGNATED STORAGE AREAS FOR THAT SOIL MATERIAL
- 5. AS REQUIRED IN THE ORDER OF CONDITIONS, ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND INSPECTED PRIOR TO THE START OF WORK AND THE LIMITS OF THE WETLAND REPLACEMENT AREA SHALL BE CLEARLY MARKED WITH WOODEN STAKES. EROSION CONTROL FENCING SPECIFIC TO THE REPLICATION AREA SHALL REMAIN IN PLACE UNTIL EXPOSED SOILS ARE VEGETATED AND STABLE. HAY BALES USED IN CONJUNCTION WITH THE PERIMETER CONTROL OR USED AS TEMPORARY STABILIZATION IN THE AREA OF THE REPLICATION AREA MUST BE FREE OF WEED SPECIES.
- 6. "O" AND "A" LAYER SOILS FROM THE WETLAND FILL AREAS, AS WELL AS AREAS OF THE UPLAND AREA IN THE MEADOW AND AS DIRECTED BY THE WETLAND SCIENTIST WILL BE STRIPPED AND STOCKPILED FOR USE IN THE REPLICATION AREA.
- 7. THE WETLAND REPLACEMENT AREA INDICATED ON THE PLAN SHALL BE EXCAVATED TO THE INDICATED SUBGRADE (SEE WETLAND REPLICATION PROFILE) BEFORE THE REPLACEMENT AREA SOILS ARE PLACED. THE WETLAND SCIENTIST SHALL BE ON-SITE TO INSPECT THE WETLAND REPLACEMENT AREA DURING THE CONSTRUCTION PROCESS AND MAY ADJUST THE FINAL GRADES IN THE WETLAND REPLACEMENT AREA BASED ON OBSERVED HYDROLOGY. WETLAND SOILS SHALL NOT BE PLACED IN THE REPLICATION AREA UNTIL THE WETLAND SCIENTIST HAS AGREED THAT THE ROUGH GRADE HAS ESTABLISHED APPROPRIATE HYDROLOGY.
- 8. THE TRANSITION ZONE BETWEEN THE WETLAND REPLACEMENT AREA AND THE SURROUNDING UPLAND PLANT COMMUNITY ADJACENT TO THE WETLAND REPLACEMENT AREA SHALL BE GRADED TO CREATE A SMOOTH TRANSITIONAL SLOPE BETWEEN THE WETLAND REPLACEMENT AREA AND THE UPLAND PLANT COMMUNITY.
- 9. SITE GRADES AND SLOPES SHALL BE CONSTRUCTED IN AGREEMENT WITH THE GRADING DETAILS SHOWN ON THE APPROVED SITE PLAN, WITH MINOR ADJUSTMENTS APPROVED IN THE FIELD BY
- 10. STOCKPILED WETLAND OR SELECTED "O" AND "A" SOILS FROM THE MEADOW AREA SHALL BE PLACED IN THE ROUGH GRADED REPLACEMENT AREA TO ESTABLISH WETLAND SOILS BETWEEN 8 AND 12 INCHES IN DEPTH. ONSITE UPLAND SOILS MAY REQUIRE SUPPLEMENTARY DECOMPOSED LEAF LITTER OR OTHER APPROVED ORGANIC MATTER, TO PROVIDE A MINIMUM 25 % ORGANIC MATTER BY VOLUME. ANY EXISTING/IMPORTED WETLAND SOIL AND SOIL AMENDMENT MATERIAL SHALL BE INSPECTED BY THE WETLAND SCIENTIST FOR ANY OBVIOUS PRESENCE OF INVASIVE/EXOTIC SPECIES PRIOR TO TRANSLOCATION TO THE SITE. IN THE EVENT OFFSITE SOIL IS USED FOR THE WETLAND SOILS, IT SHALL CONTAIN 12-18 % ORGANIC CARBON BY DRY WEIGHT.
- 11. COARSE, WOODY DEBRIS SHALL BE ADDED THROUGHOUT THE REPLACEMENT WETLAND SURFACE AREA TO ACHIEVE COVERAGE OF AT LEAST 5%.
- 12. OPTIMAL PLANTING CONDITIONS OCCUR FROM APRIL 1 MAY 15 IN THE SPRING AND SEPTEMBER 1 - OCTOBER 15. SEEDING AND PLANTING WILL OCCUR ONLY DURING THESE TIME PERIODS UNLESS APPROVED BY THE WETLAND SCIENTIST. WETLAND VEGETATION PLANTED IN THE WETLAND REPLACEMENT AREA MAY INCLUDE PLANTS SALVAGED FROM THE BORDERING VEGETATED WETLAND PROPOSED TO BE FILLED AND TRANSFERRED TO THE WETLAND REPLACEMENT AREA IF DEEMED SUITABLE BY THE WETLAND SCIENTIST. ADDITIONAL NATIVE SHRUBS WILL BE ADDED TO THE PLANTING AREA TO SUPPLEMENT THE SALVAGED MATERIAL AS IDENTIFIED IN THE PLANTING TABLE.
- 13. PROPOSED VEGETATION FOR WETLAND REPLICATION AREA. PLANTS SHALL BE PLANTED IN APPROXIMATED DENSITIES/SPACING AS IDENTIFIED IN THE TABLE, ALTHOUGH SHRUB SPECIES MAY BE CLUSTERED IN GROUPS OF 2/3 TO CREATED MORE NATURAL CONDITIONS.
- 14. PLANTS SHALL BE SOURCED FROM NEW ENGLAND WETLAND PLANTS, INC. OR EQUIVALENT. 15. A WETLAND SEED MIX SUCH AS NEW ENGLAND WETMIX BY NEW ENGLAND WETLAND PLANTS, INC., OR APPROVED EQUIVALENT, SHALL BE BROADCAST THROUGHOUT THE AREA AT AN APPLICATION RATE OF 1 LB PER 2,500 S.F. OR AS SPECIFIED BY THE MANUFACTURER, AND IT SHALL BE MULCHED WITH 1-2" THICK LAYER OF STRAW OR OTHER SUITABLE ORGANIC EQUIVALENT AND MAINTAINED UNTIL VEGETATION HAS BEEN ESTABLISHED.
- 16. UPLAND BUFFER ZONES DISTURBED AS A RESULT OF CONSTRUCTION OF THE WETLAND REPLICATION AREA SHALL BE PLANTED WITH NATIVE SHRUBS AND SAPLINGS APPROVED BY THE WETLAND SCIENTIST AND SEEDED WITH A NATIVE NEW ENGLAND CONSERVATION SEED MIX BY NEW ENGLAND WETLAND PLANTS, INC., OR APPROVED EQUIVALENT, AT AN APPLICATION RATE OF 1 LB PER 1,750 SF OR AS SPECIFIED BY THE MANUFACTURER, AND IT SHALL BE MULCHED WITH 1-2" THICK LAYER OF STRAW OR OTHER SUITABLE ORGANIC EQUIVALENT AND MAINTAINED UNTIL VEGETATION HAS BEEN ESTABLISHED.
- 17. THE WETLAND REPLICATION AREA SHALL BE INSPECTED MONTHLY BY THE WETLAND SCIENTIST UNTIL THE AREA IS 75% UNIFORMLY VEGETATED AND STABLE, AND UNTIL THE WETLAND SCIENTIST DETERMINES THAT THE RESTORATION AREA EROSION CONTROLS CAN BE REMOVED. INSPECTIONS CAN BE SUSPENDED DURING FROZEN CONDITIONS. UPON REACHING STABILITY, TWO ANNUAL INSPECTIONS SHALL BE MADE OF THE COMPLETED REPLACEMENT AREA BY THE WETLAND SCIENTIST IN COMPLIANCE WITH MASSACHUSETTS INLAND WETLAND REPLICATION GUIDELINES, MARCH, 2002 IN ORDER TO ASSESS THE SUCCESS OF THE WETLAND REPLICATION
- 18. DURING THE TWO ANNUAL INSPECTIONS OF THE REPLACEMENT WETLAND AREA, THE CONTRACTOR SHALL REMOVE BY HAND ALL INVASIVE PLANT SPECIES AS IDENTIFIED BY THE WETLAND SCIENTIST.



WETLAND REPLICATION

AREA #1

HORIZ. SCALE: 1"=10





PREPARED FOR

6 FOREST ROAD LLC

71 COMMERCIAL STREET, #263 BOSTON, MA 02109

				N
1	4/12/21	ADDRESS REVIEWER'S COMMENTS	C.M.Y.	SC
NO.	DATE	DESCRIPTION	BY	DA

MILLENNIUM ENGINEERING, INC. ENGINEERING AND LAND SURVEYING

DESG. BY: C.M.Y.

CHKD. BY: E.W.B.


62 ELM ST. SALISBURY, MA 01952 (978) 463-8980 13 HAMPTON RD. EXETER, NH 03833 (603) 778-0528


ROJECT: M193659

SITE PLAN SALISBURY, MA SHOWING 64 UNIT TOWNHOUSE COMMUNITY 6 FOREST ROAD & MEADOWVIEW LANE

WETLAND REPLICATION **DETAILS**

SHEET: C-15






Schedule											
Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens Per Lamp	Light Loss Factor	Wattage
$\hat{\circ}$	A3	18	Sternberg Lighting	1970LED-4ARC30T3- MDL03-FG	1970 Gallery Fixture; mounted at 14ft	LED	1	1970LED- 4ARC45T3- MDL03-FG.IES	6548	0.9	64.1
Ô.	A4	6	Sternberg Lighting	1970LED-4ARC30T4- MDL03-FG	1970 Gallery Fixture; mounted at 14ft	LED	1	1970LED- 4ARC45T4- MDL03-FG.IES	6705	0.9	64.5
	A5	2	Sternberg Lighting	1970LED-4ARC30T5- MDL03-FG	1970 Gallery Fixture; mounted at 14ft	LED	1	1970LED- 4ARC45T5- MDL03-FG.IES	6730	0.9	64.4

1970LED GALLERY SERIES

LED

A	7 YEAR	L
(ft²)	WARRANTY	F
IGHT	(James	5
LBS	(7)	1
	There	











RATED IP65
IP 65

	JOB NAME	
	FIXTURE TYPE	
	МЕМО	

							E	UILI	O A PAR	T NUM	BER					
	ORDE	RING	EXAM	PLE:	2A-1	970L	ED-5	-GR-4	ARC45T	5-MDL	03-SV	1-R7-PE	HSHN/C	A6/5218	P5/UBICT	Г
Mounting Config.	Fixture	Shade Edge	Top Feature	LED	сет	Туре	Driver	Lens	Optional Control Receptacle	Optional Control	Option Fuse	Option Hang- straight	Option House Side Shield	Arm See Arm Spess Sheets	Piole See Pole Opes Sheets	Finish
	-	-		-	-	-	•	+	-	-	-	-				-

Statistics				-			
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min	
Outside of Parking Lot	+	0.3 fc	4.4 fc	0.0 fc	N/A	N/A	
Roadway	+	1.3 fc	4.2 fc	0.1 fc	42.0:1	13.0:1	

0 + 0.0 + 0.1 + 0.2 + 0.2 + 0.1 + 0.1 + 0.1 + 0.1 + 0.2 + 0.2 + 0.2 + 0.1 + 0.1 + 0.1 + 0.1 + 0.1 + 0.2 + 0.2 + 0.2 + 0.1 +

+Q.1 +0.1 +0.1 +0.1 +0.1

01 0.2 0.2 0.1 0.



Site


Designer Heidi G. Connors Visible Light, Inc. 24 Stickney Terrace Suite 6 Hampton, NH 03842 4/12/2021 Scale 1"=30' Drawing No.

Summary

E-1




E:\sdskproj-2019\M193659\dwg\M193659-D.dwg 4/9/2021 1:52:20 PM EDT




Site Lighting Layout
At


Designer
Heidi G. Connors
Visible Light, Inc.
24 Stickney Terrace
Suite 6
Hampton, NH 03842
Date
4/12/2021
Scale
1"=30'
Drawing No.

Summary










SECOND FLOOR PLAN

SCALE: 1/8"=1'-0"



FIRST FLOOR PLAN

SCALE: 1/8"=1'-0"

DUPLEX 161 FEDERAL HILL ROAD HOLLIS, NEW HAMPSHIRE 03049 603-465-6960

PROJECT NO.: 1938

